

# System Unit GARNET541, IG-541 engineered extinguishing system units, 200 and 300 bar

File Number: EX28925

**COMPANY**

Utusan Deria Sdn Bhd

No. 18a, Jalan Au 5d/1, Taman Lembah Keramat  
Kuala Lumpur, Kuala Lumpur 54200 Malaysia

**SYSTEM UNIT INFO**

GARNET541, IG-541 engineered extinguishing system units, 200 and 300 bar

Engineered, Inert Gas

CLEAN AGENT EXTINGUISHING SYSTEM UNITS	VALUE
Extinguishing Agent (ASHRAE Designation)	IG-541

**MANUALS AND BULLETINS**

Part No.	Description	Date/Rev
GNIGMAL-0541	Design, Installation, Operation and Maintenance Manual	Rev. 3, dated 2023-10

**SYSTEM UNIT INFORMATION**

Operating Pressure at Temperature	Minimum Operating Temperature	Maximum Operating Temperature
200 bar @ 21 C	-20 C (-4 F)	55 C (131 F)
300 bar @ 21 C	-20 C (-4 F)	55 C (131 F)

**THESE INSTALLATIONS REQUIRE THE USE OF THE LISTEE'S FLOW CALCULATION SOFTWARE:**

Software Name/Version
GARNET541 Flow Calculation Software v4.10

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."